

Oracle

1Z0-932 Exam

Infrastructure as a Service (IaaS)

Demo

Version: 8.1

Question: 1

Which two parameters are required in a back end set's HTTP health check?

- A. response body
- B. URL path
- C. timeout
- D. port
- E. status code

Answer: BD

Question: 2

Which two are true for achieving High Availability on Oracle Cloud Infrastructure?

- A. Store your database across multiple regions so that half of the data resides in one region and the other half resides in another region.
- B. Attach your block volume from Availability Domain 1 to a compute instance in Availability Domain 2 (and vice versa) so that they are highly available.
- C. Configure your database to have Data Guard in another Availability Domain in Sync mode within a region.
- D. Store your database files on Object Storage so that they are available in all Availability Domains in all regions.
- E. Distribute your application servers across all Availability Domains within a region.

Answer: CE

Question: 3

Which two configuration formats does Terraform support?

- A. YAML
- B. JSON
- C. HCL
- D. XML

Answer: BC

Question: 4

At the end of a terraform apply operation, what is the default output?

- A. nothing by default
- B. statistics about what was added, changed, and destroyed
- C. the entire state file
- D. statistics and the values of outputs

Answer: B

Question: 5

You have created a public subnet in a VCN, and your public subnet has a Route Table, a Security List, and an Internet Gateway. However, none of the compute Instances can connect to the Internet. Which two are possible reasons for the connectivity Issue?

- A. There is no Dynamic Routing Gateway (DRG) associated with the VCN.
- B. The Route Table has no default route for routing traffic to the Internet Gateway.
- C. There is no stateful ingress rule in the Security List associated with the public subnet.
- D. There is no stateful egress rule in the Security List associated with the public subnet.

Answer: BD

Question: 6

You want an instance in your compartment to make API calls to other services within Oracle Cloud Infrastructure without storing credentials in a configuration file. What do you need to do?

- A. No action is required. By default, all VM instances are created with an Instance Principal.
- B. Instances cannot access service outside their compartment.
- C. VM instances are treated as users. Create a user and assign the user to that VM Instance.
- D. Create appropriate matching rules in the Dynamic Group to create an instance Principal.

Answer: D

Question: 7

Which three must be configured for a load balancer to accept Incoming traffic?

- A. a listener
- B. a back-end server
- C. a back end set
- D. a security list that is open on a listener port
- E. a certificate

Answer: ACD

Question: 8

Which two statements are true about Oracle Cloud Infrastructure Compute Service?

- A. You can launch a virtual or bare metal Instance by using the same Launch Instance API.
- B. You cannot launch a bare metal server in Oracle Cloud Infrastructure Compute Service.
- C. You can attach a block volume in an Availability Domain other than your compute Instance.
- D. You can share custom Images across tenancies and regions.

Answer: AB
