

Implementing and Configuring Cisco Identity Services Engine

Questions & Answers Demo

E. TCP 8905

Version: 24.0

Question: 1	
What are two components of the posture	e requirement when configuring Cisco ISE posture? (Choose two)
A. updates	
B. remediation actions	
C. Client Provisioning portal D. conditions	
E. access policy	
L. decess poncy	
	Answer: B, D
Explanation:	
Question: 2	
What is a method for transporting securi	ty group tags throughout the network?
A. by enabling 802.1AE on every network	device
B. by the Security Group Tag Exchange Pr	
C. by embedding the security group tag in	
D. by embedding the security group tag i	n the 802.1Q header
	Answer: B
Explanation:	
Question: 3	
Which two ports must be open between ISE? (Choose two).	n Cisco ISE and the client when you configure posture on Cisco
A. TCP 8443	
B. TCP 8906	
C. TCP 443	
D. TCP 80	

	Answer: A, E
Explanation:	
Question: 4	
Which profiling probe collects the user-agent string?	
A. DHCP	
B. AD	
C. HTTP	
D. NMAP	
_	Answer: C
Explanation:	Allower. C
Question: 5	
Which supplicant(s) and server(s) are capable of supporting EAP-CHAINING?	
A. Cisco AnyConnect NAM and Cisco Identity Service Engine	
B. Cisco AnyConnect NAM and Cisco Access Control Server	
C. Cisco Secure Services Client and Cisco Access Control Server	
D. Windows Native Supplicant and Cisco Identity Service Engine	
_	Answer: A
Explanation:	