

Cisco

Exam 650-474

Introducing Cisco Identity Services Engine for System Engineer Exam

Verson: Demo

[Total Questions: 10]

Question No : 1

Which statement about Cisco Identity Services Engine high availability is true?

- A. Monitoring nodes are deployed in an active/active mode. One node serves as primary. All logs are sent automatically to both HA monitoring nodes.
- B. Administration nodes are limited to two and are deployed in an active/standby mode.
- C. Secondary Administration node automatically becomes primary in the event of primary node failure.
- D. Monitoring nodes are deployed in an active/standby mode. All logs sent to the primary are replicated to the secondary node.
- E. Users are served from the secondary Monitoring node only if the active Monitoring node fails.

Answer: D

Question No : 2

Which types of design are required in the Cisco ISE ATP program?

- A. schematic and detailed
- B. preliminary and final
- C. high-level and low-level designs
- D. top down and bottom up

Answer: C

Question No : 3

Which methods can be used to create usernames?

- A. general or random
- B. RFC2381 or IEEE 1493
- C. Knopf or WS naming
- D. manual or Ruby

Answer: A

Question No : 4

Which ISE persona presents the Guest portal page for Central Web Authentication?

Select exactly 1 answer(s) from the following:

- A. Policy Service
- B. Admin
- C. Monitoring
- D. Inline Posture

Answer: A

Question No : 5

Which two roles can be deployed across more than two nodes in an instance? (Choose two.)

- A. Monitoring
- B. Administration
- C. Inline Posture
- D. Pokey Service

Answer: A,B

Question No : 6

Which existing platforms support data migration to Cisco ISE 1.0?

- A. NAC4.X
- B. ACS 4.X
- C. NAC 3.X
- D. ACS 5.X

Answer: A

Question No : 7

Which two deployment methods are supported with Cisco ISE 1.0 with RADIUS NAC?

(Choose two.)

- A. Unified Wireless
- B. HREAP - Local Switched
- C. HREAP - Central Switched
- D. Autonomous

Answer: A,C

Question No : 8

In the Cisco ISE ATP program, what must the sales team submit to begin the sales process?

- A. a new product-hold waiver
- B. high-level and low-level designs
- C. a preliminary design and a request for equipment release
- D. a high-level design and BoM

Answer: B

Question No : 9

What is the maximum number of supported endpoints on an appliance in stand-alone mode?

- A. 5,000
- B. 7,500
- C. 10,000
- D. 2,000

Answer: D

Question No : 10

Which option is the default authentication priority on a Cisco switch?

- A. MAB, 802.1X, Web-Auth
- B. 802.1X, MAB, Web-Auth
- C. MAB Web-Auth, 802.1X
- D. 802.1X, Web-Auth, MAB

Answer: B