
Question:1

Which of the following is the correct code for assigning a custom template file using layout XML?

- A.<block type="core/text_list" name="custom.template" template=" folder/custom_template.phtml"/>
- B.<block type="core/template" name="custom template" template=" folder/custom_template.phtml"/>
- C.<block type="block/template" name="custom template" template=" folder/custom_template.phtml"/>
- D.<block type="cms/block" name="custom.template" template=" folder/custom_template.phtml"/>
- E.<block type="block/html" name="custom template" template=" folder/custom_template.phtml"/>

Answer: B

Question:2

You want to create a wrapper block that uses an HTML tag name which is set by the action `setHtmlTagName`. The wrapper block should render all its child blocks within the HTML tag. Which block type should you use to create the wrapper block?

- A.page/html
- B.page/wrapper
- C.page/div wrapper
- D.page/html_wrapper

Answer: D

Question:3

You want to figure out which phtml-files are rendering in the front end. Which developer tool helps you do that?

- A.Profiler
- B.Exception.log
- C.Block Class Names
- D.Template Path Hints
- E.System.log

Answer: D

Question:4

Which is the correct order of the three types of translations by priority (1 = highest, 3 = lowest)?

- A. 1. Database (Inline) translation
 - 2. Module translation
 - 3. Theme translation
- B. 1. Database (Inline) translation
 - 2. Theme translation
 - 3. Module translation
- C. 1. Module translation
 - 2. Database (In line) translation
 - 3. Theme translation
- D. 1. Theme translation
 - 2. Database (In line) translation
 - 3. Module translation

Answer: B

Question:5

Which piece of code creates a url that links to the store pages in transactional email templates?

- A.{{store url=" "}}
- B.{{ store_page url=" " } }
- C.{{ store_url=" " } }
- D.{{ store_name url=" " } }

Answer: A

Question:6

Your project, which uses prototype.js, contains the JavaScript class Photoviewer (see EXAMPLE, below). Which one of the following code samples will create a class called AdvancedPhotoViewer that extends Photoviewer?

EXAMPLE:

```
var PhotoViewer = Class.create();
```

- A.var AdvancedPhotoViewer = new PhotoViewer()
- B.AdvancedPhotoViewer.prototype = Object.extend (new PhotoViewer ()
- C.var AdvancedPhotoViewer = Class.extend (PhotoViewer)
- D.AdvancedPhotoViewer = PhotoViewer.extend ()

Answer: B

Question:7

Which element in layout XML specifies a method to be called on a referenced or newly defined block?

- A.<action>
- B.<call>
- C.<change>
- D.<method>
- E.<update>

Answer: A

Question:8

Which one of these code samples will assign a root template to a specific page of native Magento?

A.

```
<default>
    <reference name="catalog_product_view">
        <action method="setTemplate">
            <template>page/3columns.phtml</template></action>
        </reference>
    </default>
```

B.

```
<cms_index_index>
    <reference name="default">
        <action method="setTemplate">
            <template>page/3columns.phtml</template></action>
        </reference>
    </cms_index_index>
```

C.

```
<customer_account_login>
    <reference name="template">
        <action method="setTemplate">
            <template>page/3columns.phtml</template></action>
        </reference>
    </customer_account_login>
```

D.

```
<catalog_product_view>
    <reference name="root">
        <action method="setTemplate">
            <template>page/3columns.phtml</template></action>
        </reference>
    </catalog_product_view>
```

Answer: D

Question:9

You want to create a new “screendesign” package based on the “default” package’s “default” theme. Which ONE of the following steps do you have to take?

- A.Copy app/design/base to app/design/screendesign
- B.Create an empty folder app/design/frontend/screendesign and copy app/design/frontend/default/default into it
- C.Create skin/frontend/screendesign, then copy the CSS and images folders and their files from /skin/frontend/default/default/ to skin/frontend/screendesign/default
- D.Inside app/design/frontend and skin/frontend, copy the folder “default” to the folder “custom”; then rename custom/default to custom/screendesign in both places
- E.Create app/design/frontend/default/screendesign

Answer: C

Question:10

Which ONE of the following adds links to the top links navigation?

A.

```
<block name="top.links" type="page/template_links">
    <mylink>
        <label>I HAS A SHOP</label>
        <url>http://magento.com</url>
        <title>ITZ A MAGENTO</title>
    </mylink>
</block>
```

B.

```
<action method="addLink" block="top.links">
    <label>I HAS A SHOP</label>
    <url>http://magento.com</url>
    <title>ITZ A MAGENTO</title>
</action>
```

C.

```
<reference name="top.links">
    <link>
        <label>I HAS A SHOP</label>
        <url>http://magento.com</url>
        <title>ITZ A MAGENTO</title>
    </link>
</reference>
```

D.

```
<update handle="top.links" method="addLink">
    <label>I HAS A SHOP</label>
    <url>http://magento.com</url>
    <title>ITZ A MAGENTO</title>
</update>
```

Answer: B
