

# **McAfee**

## **MA0-101 Exam**

**McAfee Certified Product Specialist- NSP Exam**

### **Questions & Answers Demo**

---

**Question: 1**

---

Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

---

**Answer: B**

---

---

**Question: 2**

---

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

- A. Signature based
- B. Pattern matching
- C. Denial of Service
- D. Remediation

---

**Answer: C**

---

---

**Question: 3**

---

Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

- A. sensor perf-debug 100
- B. sensor perf-debug on 100
- C. sensor perf-debug Interface all 100
- D. sensor perf-debug assert 100

---

**Answer: A**

---

---

**Question: 4**

---

What type of encryption is used for file transfers between the Sensor and the Manager?

- A. SSL with RC4
- B. SSL with MD5
- C. SSL with RC4 and MD5
- D. DES

---

**Answer: D**

---

---

**Question: 5**

---

When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?

- A. MAC address
- B. IP address
- C. DNS
- D. Subnet

---

**Answer: B**

---

---

**Question: 6**

---

What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

- A. arp spoof status
- B. arp spoof enable
- C. arp dump
- D. arp flush

---

**Answer: C**

---

---

**Question: 7**

---

DoS detection is implemented in which of the following modes? (Choose two)

- A. Learning mode
- B. Configuration mode
- C. Threshold mode
- D. Bidirectional mode

E. Inbound mode

---

**Answer: A, C**

---

---

**Question: 8**

---

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

---

**Answer: C**

---

---

**Question: 9**

---

Which port is correctly defined for the Alert Channel on the Network Security Manager?

- A. 8500
- B. 8501
- C. 8502
- D. 8504

---

**Answer: C**

---

---

**Question: 10**

---

In double VLAN tagging, a second VLAN tag that is inserted into the frame is referred to as which of the following?

- A. Customer Identification tag (CD)
- B. VLAN Identification tag (VID)
- C. Outer Identification tag (OID)
- D. Inner Identification tag (HD)

---

**Answer: A**

---